

CLMPTO 10/06/04 JW

Amend Claims 3,9,11,12,14-17

1. (original) Method of selecting at least one transmission channel from a plurality of transmission channels, in a time division multiple access protocol, characterized primarily in that it comprises in:

- * receiving for each channel a periodic indication of the transmission quality of that channel;

- * storing these indications for each channel during a time window;

- * selecting at least one channel that has the best current transmission quality indication position relative to the transmission quality indications stored for that channel during the time window.

- *

2. (original) Method of selection according to Claim 1, characterized in that the step of selecting at least one channel is carried out from a plurality of channels over which data are to be transmitted and from these channels at least one channel that has the best or amongst the best current transmission quality indication position relative to the transmission quality indications stored for that channel during the time window.

3. (currently amended) Method according to Claim 1 or Claim 2, characterized in that it comprises, during a step (80), in determining the number

BEST AVAILABLE COPY

of channel k , the size of the time window T and the initial values of the transmission qualities of each channel during the time window and in that these parameters may be updated by interrupting the method at moments chosen by a reinitialization finite state machine, particularly when the number of channels K changes due to the activity of the users.

3. (original): Method according to Claim 3, characterized in that it consists in executing, during each unit of time, the said series of instructions comprising in:

- * executing a loop (81) to determine for each channel i the position P_i of the current transmission quality indication relative to those stored for that channel during the time window;
- * selecting, during a step (82), from the channels for which data are to be transmitted at least one channel i that has the best or amongst the best values of P_i ;
- * during a step (83), giving transmission authorization at least to the channel i .

4. (original): Method according to Claim 4, characterized in that the loop (83) consists, for each channel i , where i is from 1 to N , in:

- * acquiring, during a step (83), a transmission quality indication of the channel i , that is to say:
- * initializing, during a step (83), a value of position P_i at 1;
- * executing a second loop (84) in order to determine a value indicative of the position P_i ;

- executing a third loop (81) in order to update the transmission quality indicators of the channel (8_1) during the time window.

4. (original) Method according to Claim 3, characterized in that the loop (82) consists, for each loop index (k, where k is from 1 to N), in:

- evaluating the result of a test (73) defined by the relation: $dist_k > dist_c$;
- incrementing the indication of position (71) by one unit during a step (83) if the result of the test (73) is positive;
- otherwise, evaluating the result of a test (72) defined by the relation $dist_k \sim dist_c$ AND RAND < 1; where RAND is a function returning a random variable, in particular uniformly distributed over the interval [0,1];
- executing the step (83) of incrementing the indication of position (71) if the result of the test (72) is positive.

5. (original) Method according to claim 3, characterized in that the loop (83) consists, for each loop index (k, where k is from 1 to N), in:

- assigning the previously stored value $dist_{k-1}$ to the variable $dist_k$ using a step (84).

6. (original) Method according to Claim 4, characterized in that a suspension step or a random choice is applied to the step (84) when several active channels have a minimum indication of position (71).

7. (currently amended) Method according to Claim 2, characterized in that if several

channels are authorized to transmit simultaneously, the step (24) consists in selecting from the channels for which data are to be transmitted those that have the best position (23) and in that a step (25) consists in giving transmission authorization to these channels.

10. (original) Method according to claim 8, characterized in that the second test (22) comprises a predetermined comparison to decide the indication of position (23) when the current transmission quality indication of the channel, that is (21), is equal to one or more values of the nine numbers.

11. (currently amended) Method according to claim 9, characterized in that the steps (21, 22, 23) are processed in parallel and not sequentially.

12. (currently amended) Communication system using the method of claim 1, characterized in that it comprises:

- * a method for receiving, for at least one channel, a periodic indication of transmission quality of that channel;
- * a memory for storing the transmission quality indications of each channel during a time window;
- * a computing circuit to determine, for each channel for which a periodic indication of transmission quality has been received, the position of the current transmission quality indication of that channel relative to those stored for that channel during the time window;
- * a circuit for selecting at least one transmission channel that has the best current transmission

quality indication position relative to those stored for that channel during the time window.

13. (originally amended): Communication system according to Claim 11, characterized in that the circuit for selecting at least one transmission channel comprises a means of selecting channels over which data are to be transmitted and that have the best or the amongst the best current transmission quality indication position(s) relative to the positions stored for that channel in those channels during the time window.

14. (currently amended): Communication system according to Claim 11, characterized in that it comprises at least one circuit (A1) for acquiring the transmission quality signal of the channel (C₁), that is C1(t), on the date t.

15. (currently amended): Communication system according to Claim 11, characterized in that it comprises at least one memory (A2) consisting of P blocks, each block (A2,k) containing the value of transmission quality of the channel (C₁) on the date (t-k), that is C1(t-k), where k is from 1 to P.

16. (currently amended): Communication system according to Claim 11, characterized in that it comprises at least one set (A3) of at most P comparison circuits, each circuit (A3,k) comparing the current transmission quality indication contained in at least the circuit (A1) with the transmission quality indication on the date t-k contained in the memory block (A2,k), where k is from 1 to P.

17. (currently amended): Communication system according to Claim 11, characterized in that it comprises at least one adder (A4), to the input of which is connected the output of each comparison circuit (A3,k), where k is from 1 to P, and an independent input always giving the value 1.

This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.